

KS-M220

> Multi-Functional Kiosk



Features



- Real modular and flexible with Plug and Go design
- 21.5" Full HD TFT-LCD
- Selectable for cost-effective Celeron and performance Core-i CPU
- Aluminum structure and high texture glossy finish
- Feature-rich devices to fulfill different demands
- Reserve customized design for credit card and contactless payment
- Customizable payment terminal bracket
- Easy maintenance via modular design

Applications

- Retail and chain store service kiosk
- Food ordering and payment kiosk
- Ticket selling service kiosk
- Information kiosk
- Kitchen display kiosk

Highlights



*All information contained in this document is subject to change without prior notice. Please log on www.protech.com.tw to acquire latest information.

Specifications



System	CPU	Hi-End: Intel® Core i5-7300U / i3-7100U / Pentium® 4415U Entry: Intel® J3455 CPU
	Memory	Hi-End: 1 x DDR4 SO-DIMM slot (Default: 4GB) or Entry: 1 x SO-DIMM socket, supporting 1600/1867 DDR3L memory up to 4G (non-ECC)
	Storage	1 x 2.5" SATA HDD (Default: 500GB)
	Network	2 x Gigabit 10/100/1000 Base-T Fast Ethernet (RJ45)
	Power Supply	100-240V available
	System Weight	KDS: 13.81 kg M-type: 31.71 kg M-type stand: 31.43 kg Cash type: 75.35 kg
	Dimensions (W x H x D)	M-type: 377 x 585 x 160 mm (without stand) 450 x 1636 x 450 mm (with stand) KDS: 377 x 585 x 70 mm Cash pay: 377 x 1704.6 x 282 mm
O.S. Support	Windows 10	
Operating Display	LCD	21.5" TFT LCD
	Max. Resolution	FHD
	Brightness	250 cd/m ²
	Touchscreen	Projected capacitive touch
	Viewing Angle	Horizontal: (R) 89° / (L) 89° Vertical: (U) 89° / (L) 8°
Add-ons	Face Camera (optional)	2.1M FHD Camera, Gotek NC0-O62FR-XF01
	Barcode Scanner (optional)	1D / 2D Barcode
	Thermal Printer (optional)	2" or 3" Standalone Thermal printer
	Wi-Fi Module (optional)	2T2R PCIe Half-Mini Card
Environment	EMC & Safety	CE / FCC
	Operating Temp.	5°C~35°C
	Storage Temp.	0°C~60°C
	Humidity	20%~85% (no condensation)

Dimensions

