

SP-6565

Intel® 7th / 6th Gen. Core™ Fanless and High Performance 15" Flat Panel PC




Features



- Intel® 7th / 6th Gen. Core™ i7 / i5 / i3 and Pentium® / Celeron® desktop processor (LGA1151)
- 2 x DDR4 2133MHz SO-DIMM memory up to 32GB
- 2 x 2.5" SATA III HDD/SSD with RAID 0/1 (Q170)
- 2 x Mini PCIe slots, 1 x PCIe (x4) slot (Q170)
- 2 x GbE LAN, PoE as option
- Wide-ranged voltage DC In 9~36V
- Front panel IP65 design
- Aluminum front bezel
- Supports 5-wire resistive touchscreen or projected capacitive touchscreen

Specifications



System

CPU Support	Core™ i7-6700TE, Quad Core, 2.4GHz, 8M cache Core™ i5-6500TE, Quad Core, 2.3GHz, 6M cache Core™ i3-6100TE, Quad Core, 2.7GHz, 4M cache Pentium® G4400TE, Dual Core, 2.4GHz, 3M cache Celeron® G3900TE, Dual Core, 2.3GHz, 2M cache
Chipset	Intel® Q170/H110
Memory Support	2 x DDR4 2133MHz SO-DIMM sockets (up to 32GB)
Watchdog	1~255 seconds watchdog timer selectable
Storage	2 x 2.5" SATA HDD/SSD (support RAID 0/1 in Q170 SKU only)
Front Bezel	Aluminum
IP65	Yes (for front panel only)
Power Input	DC In 9~36V
Operating System	Windows 10 IoT Enterprise LTSB 2016 64bit / Windows 8.1 (64bit) / Windows 7 (64bit) / Ubuntu 16.04 LTS / Linux Ubuntu 14.04 (64bit)
Dimensions	364.43 x 278.88 x 117.80 mm (W x H x D)
System Weight	10 kg (TBD)
Mounting Support	Wall mount / VESA 100 / Panel mount
Certifications	FCC / CE

Display

LCD	15" TFT LCD (LED) resolution XGA 1024 x 768
Touchscreen	5-wire resistive touchscreen or projected capacitive touchscreen (USB interface)

Applications

- Automation
- Retail
- Food Service
- Banking
- Information
- Hospitality
- Gaming


I/O Ports

Display	1 x DVI-I (DVI-D+VGA)
USB	4 x USB 3.0
Audio	1 x Line In / 1 x Line Out / 1 x Mic In
LAN	2 x LAN (PoE IEEE 802.3af optional), Wake-On-LAN, PXE LAN 1: Intel® PHY 219LM (10/100/1000 Mbps) LAN 2: Intel® LAN 210AT (10/100/1000 Mbps)
Serial Ports	COM 3/4 for RS232 COM 1/2 for RS232/422/485 (selectable under BIOS) [COM 1/2 for +5V/+12V/RI selectable by jumper]
Storage	2 x 2.5" SATA III HDD/SSD drive space
Digital I/O port	8 in / 8 out, DSUB-25 type or 16 pin terminal block (optional)
Expansion Slots	1 x full-sized Mini PCIe (Mini PCIe, USB and SIM signal) 1 x half-sized Mini PCIe (Mini PCIe and USB signal) 1 x SIM card slot 1 x CFast slot
Antenna Hole	3 x antenna holes
Power On/Off	1 x power button 1 x remote switch
LED	2 x PoE active LED (optional)
I ² C Bus	1 x I ² C Bus port (optional)


Environment

Operating Temp.	SSD: (w/o PoE) 0°C~45°C (32°F~113°F) (Ambient with airflow) (with PoE) 0°C~40°C (32°F~104°F)
Storage Temp.	-20°C~80°C (-4°F~176°F)
Humidity	20%~90%

Highlights



I/O Panel View



Dimensions

