

# MP-1060

› Printer

## Features



- Printing speed 200 mm/sec
- RS232+USB/Ethernet interface available
- Ease-of-use features including drop-in paper loading
- ESC/POS command compatible
- Two drawer kick-out
- Wall mountable with optional kit
- Drop & print paper loading
- Print alarm buzzer
- Various Interface Options
- OPOS driver supported
- Stores/Prints logo Images
- Barcode and bitmap printing capability
- Paper-end sensor and paper near-end sensor available
- Accessories and options with melody box, splash proof cover, wall-mount and cable cover, etc



## Specifications

|                         |   |
|-------------------------|---|
| Model                   | MP-1060   |
| Printer Method          | Thermal line  |
| Paper Width             | 80+0, -1 mm   |
| Interface               | Combo with USB/Serial   |
| Number of Columns       | 64 (12 x 24) / 48 (9 x 17) / 24 (24 x 24) C/L                           |
| Buffer                  | 4K  |
| SRAM                    | 128K  |
| Flash                   | 2MB   |
| Print Speed             | 200 mm/sec  |
| Fast Feed Speed         | 200 mm/sec  |
| Character Structure     | Alphanumeric 95<br>International 32 128 x 8 graphic,<br>Big-5, Japanese |
| Head                    | 100KM   |
| Cutter                  | 1.5 million cuts  |
| Power Supply            | 24V   |
| Environmental Condition | Humidity  |
| Operating               | 10%~90% RH  |
| Storage                 | 10%~90% RH expect for paper   |
| Weight                  | Approx. 1.6 kg  |
| Detect Sensor           | Paper end and near end sensor   |
| Dimensions              | 140 x 146 x 123 mm (W x H x D)  |

\*All information contained in this document is subject to change without prior notice. Please log on [www.protech.com.tw](http://www.protech.com.tw) to acquire latest information.

[www.protech.com.tw](http://www.protech.com.tw)